



# DAY PUBLIC SCHOOL

## KAILASH HILLS, NEW DELHI



CBSE Affiliation No.: 2730186

School ID.: 1925262

Ref. No. DAVPSKH/ 24-25/22478

03/02/25

### TENDER NOTICE

1	Name of the works	Flooring, Tiling, False ceiling and addition of one room over Room No. 16, with tiles up to 5 feet.
2	Time of completion	2-3 months
3	Date of Tender Notification	03-02-2025
4	Last Date/Time for Receipt of Bids	07-02-2025
5	Cost of Tender Document	Rs 2500/-
6	Estimated value of tender	Rs 12,72,524/-
7	Name and Address of office Inviting Tender	DAV Public School, Near C – block, Kailash Hills, Delhi - 110065
8	Contact Number	011-46544839, 011-26842283

### GENERAL TERMS & CONDITIONS

1. The school shall not be liable to pay any tax, freight etc. which has not been expressly stipulated in the quotation in the event of acceptance of the quotation. The school shall deduct TDS as per rules of Income Tax Department, Government of India
2. The undersigned does not bind him to accept the lowest quotation and reserves the right to accept, the quotation in whole or in part i.e., with respect to the entire article mentioned in the attached statement or in respect of one or more than one articles specified in the attached statement as he/she may decide.
3. On acceptance of the quotation it will become a contract and the contractor shall be bound by the terms and conditions of the quotation as well. Contractor must fulfill the terms and conditions of Government of Delhi as well as Govt. of India.
4. The quantity of articles indicated in the attached statement may be increased or decreased at the discretion of the undersigned without assigning any reason thereof.

**MANAGED BY - DAV COLLEGE MANAGING COMMITTEE, CHITRA GUPTA ROAD, DELHI**

**Address : DAV Public School, Kailash Hills, near 'C' Block Market, East of Kailash, New Delhi-110065**

**Phone : 011-46544839, 011-26842283 E-mail : info.davkailashhills@gmail.com, davkhills@hotmail.com Website : www.davkailashhills.com**



# DAV PUBLIC SCHOOL

## KAILASH HILLS, NEW DELHI



CBSE Affiliation No.: 2730186

School ID.: 1925262

Ref. No. DAVPSKH/24-25/22478

03/02/25.

5. The rates quoted by the contractor shall hold good upto finishing of the renovation Works. No amendment will be accepted in the rate of renovation.
6. The description of the said renovation works in details can be had from the office of the Principal of DAV Public school, Kailash Hills, Delhi. The payment will be made to the contractor through A/c payee cheque as per the running bills submitted after the finishing of the work and duly approved by the architect.
7. Quotations which do not comply with the above conditions are liable to be rejected.
8. Non-completion of works within the stipulated time, the contractor will be liable to pay penalties as decided by the Building sub-committee, except the special circumstances if any.
9. Defect Liability Period : A security deposit of 10% to be deducted from the final bill upto defect liability period i.e. 12 months.
10. The rates are inclusive of all taxes and duties.
11. Work should be carried as per CPWD specifications.
12. No damage is caused to school property while execution of work otherwise the contractor will be liable to make for loss/damage.
13. The contractor should follow all compliances of local authorities i.e. MCD/DDA etc.

*Gang*  
PRINCIPAL

MANAGED BY - DAV COLLEGE MANAGING COMMITTEE, CHITRA GUPTA ROAD, DELHI

Address : DAV Public School, Kailash Hills, near 'C' Block Market, East of Kailash, New Delhi-110065

Phone : 011-46544839, 011-26842283 E-mail : info.davkailashhills@gmail.com, davkhills@hotmail.com Website : www.davkailashhills.com

**BOQ for Interior Work & One new room over Room No. 16, Ground Floor, at D.A.V. Public School  
Kailash Hill, New Delhi.**

S. No.	DSR Code No.	Description of Items	Qty.	Unit	Rate	Amount
1	11.26	Kota stone slab flooring over 20mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab, including rubbing and polishing complete with base of cement mortar 1:4 (1 cement : 4 coarse sand):				
	11.26.1	25 mm thick	80	Sqm		
2	11.27	Kota stone slabs 20mm thick in risers of steps, skirting, dado & pillars laid on 12mm (average) thick cement mortar 1:3 (1 cement : 3 coarse sand) and jointed with grey cement slurry mixed with pigment to match the shade of slabs, including rubbing and polishing.	10	Sqm		
3	8.31	Providing and fixing 1st quality ceramic glazed wall tiles conforming to	98	Sqm		
4	8.2	Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing of edges to give high gloss finish etc. complete at all levels.				
4.1	8.2.2					
	8.2.2.1		4.7	Sqm		
2	15.23					
	15.23.1		5.00	Sqm.		
	15.23.2		5.00	Sqm.		
3	15.2	Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.				
	15.2.2	Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix)	6.00	Cum		
4	15.56	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead	80.00	Sqm.		
5	15.60	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, all loads including all lifts involved. Note:- Malba quantity is equal to dismantled material / items.	30.00	Cum		
6	13.14	15mm cement plaster 1:2 (1 cement : 2 stone dust) on the rough side of single or half brick wall.	150.00	Sqm.		
7	13.80	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. Make :- JK., Birla	150.00	Sqm		
8	13.83	Wall painting with premium acrylic emulsion paint of interior grade, having VOC (Volatile Organic Compound ) content less than 50 grams/ litre of approved brand and manufacture, including applying additional coats wherever required to achieve even shade and colour.				
	13.83.1	One coat	1	Sqm		
	13.83.2	Two coats	180	Sqm		
9	1.10	Wiring for light point/fan point/exhaust fan point/call bell point with 1.5 sqmm FRLS PVC insulated copper conductor single core cable in surface/recessed medium class PVC conduit, with modular switch, modular plate, suitable GI box and earthing the point with 1.5mm sq.mm FRLS PVC insulated copper conductor single core cable etc. as required.				
	1.10.3	Group C	18	nos.		

10	19	Supply, Installation, Testing and Commissioning of 1200 mm sweep, BEE 5 star rated, ceiling fan with Brush Less Direct Current (BLDC) Motor, class of insulation : B, 3 nos. blades, 30 cm long down rod, 2 nos. canopies, shackle kit, safety rope, copper winding, Power Factor not less than 0.9, Service Value (CM/M/W) minimum 6.00, Air delivery minimum 210 Cum/Min, 350 RPM (tolerance as per IS : 374 - 2019), THD less than 10%, remote or electronic regulator unit for speed control and all remaining accessories including safety pin, nut bolts, washers, temperature rise = 75 degree C (max.), insulation resistance more than 2 mega ohm, suitable for 230 V, 50 Hz, single phase AC Supply, earthing etc. complete as required.	8	nos.		
11		Supply, Installation, Testing and Commissioning of following surface/recessed type fluorescent tube lighting fixtures complete with lamps, control gear and low cost CW ballasts, ceiling fan and bracket fans (make : phillips, wipro, Syska, havells or equivalent				
11.1		4'-0" LED surface light	8	nos.		
11.2		2'x2' recessed LED light panel	12	nos.		
12	26.22	Providing and fixing false ceiling at all heights with integral densified calcium silicate reinforced with fibre and natural filler false ceiling tiles of Size 595x595 mm of approved texture, design and patterns as per CPWD Specification 2019, to be laid in true horizontal level suspended on interlocking metal T-Grid of hot dipped galvanised iron section of 0.33 mm thick (galvanized @ 120 grams per sqm including both sides) comprising of main-T runners of size 24x38 mm of length 3000 mm, cross - T of size 24x32 mm of length 1200 mm and secondary intermediate cross-T of size 24x32 mm of length 600 mm to form grid module of size 600 x 600 mm, suspended from ceiling using galvanised mild steel items (galvanizing @ 80 grams per sqm) i.e. 12x50 mm long dash fasteners, 6 mm dia fully threaded hanger rod upto 1000 mm length and L-shape level adjuster of				
13	26.22.2	With 15 mm thick tegular/butt edged without perforation plain/designer light weight calcium silicate Anti-Microbial Bio-Safe coated false ceiling tiles Confirming to JIS-Z2801 and ASTM G-21	80.00	Sqm		
14	15.13	Taking out doors, windows and clerestory window shutters (steel or wood) including stacking within 50 metres lead : Of area 3 sq. metres and below	1.00	each		
15*		Slab casting in RCC including steel, ISMB, cement concrete in Design Mix as per instructions at site. Slab area to be considered for measurement. (Approx. Slab Area : 45sqm)	1.00	LS		
16*		Slab casting in RCC including steel, cement concrete in Design Mix as per instructions at site. Slab area to be considered for measurement to include walls, windows, doors, plaster, electrical conduiting, waterproofing, parapet wall (Approx. Slab Area : 45sqm)	1.00	LS		
					<b>Total</b>	<b>0.00</b>
<b>Notes : All the rates are inclusive of GST</b>						

	All the rates are as per DSR 2023 & DSR 2022 (Electrical) wherever DSR code number is mentioned. The school may negotiate on the above-mentioned rates from the contractors as this is a cost estimate.	
	Existing points with minor alterations are to be used for fans and surface lights.	